



## Specifications



AnyShop PRO	
<b>CPU</b>	Intel Atom processor D2550 (1MB Cache, 1.86 GHz, Dual Core for Cedarview-D)
<b>Chipset</b>	Intel NM10
<b>Storage</b>	SATA 2 (3Gb/s) 2.5 inch HDD or SSD, Support AHCI
<b>Memory</b>	DDR3-1066MHz SODIMM 2GB (MAX. 4GB)
<b>Graphic</b>	Integrated Intel GMA HD 3650
<b>Display</b>	
Resolution	15" LED Backlight TFT-LCD 250 cd/m <sup>2</sup> (1024 x 768 resolution)
Touch screen	5-wired Resistive Touch
<b>Internal I/O</b>	
USB	3 Ports (reserved for touch controller, SCR EMV card, MSR controller)
Serial port	COM 5 (reserved for cash drawer port) & COM 6 (reserved for MSR)
Display port	VGA & COM 4 (reserved for CDP)
Extension slot	Mini PCIe
Primary display	24bit LVDS
Speaker	2 x 0.8W (Stereo)
<b>External I/O</b>	
USB	Rear 4 (USB 2.0 x 4 ports)
PS/2	1 Port (reserved for Keyboard & Mouse)
Serial port	COM 1 ~ 3 with 5V/12V power output on 9pin
LAN	Realtek RTL 8111E Ethernet Controller
Audio	Realtek ALC 892 / Line-out, Mic-in
Display port	VGA x 1 port
<b>Options</b>	
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track
Side USB	2 Ports (USB 2.0 x 2 ports)
SCR	EMV level 1
Dallas	Dallas I-button reader
Customer display	VFD type (20 x 2)
2nd LCD	10.1" LCD or 12.1" LCD (1024 x 768 resolution)
WiFi	Mini PCIe for wireless LAN
<b>Operating Temperature</b>	0°C ~ 40°C at 10% ~ 80% humidity
<b>Storage Temperature</b>	-20°C ~ 60°C at 10% ~ 80% humidity
<b>Qualification</b>	CE, FCC, KC
<b>Power</b>	Adaptor 12V, 5A
<b>OS Support</b>	Windows XP/Vista, Windows 7, POS Ready 2009/7
<b>Dimension (WxHxD)</b>	384 x 381 x 263(mm), 15.1 x 15 x 10.3(inch)

\* Product specifications may differ according to region and may be changed without prior notice.