



- Jam-Free Paper Design
- Print Speed Up to 200mm/sec
- Specially Designed Font Provides Superior Readability
- Easy Maintenance
- High Resolution to 203dpi
- Dual USB/Serial Ports
- Easy Paper Loading
- Available Extension Melody
- Windows & OPOS Drivers
- Epson Compatible

## Specifications



A7		
Printing method	3" Jam-free direct thermal	
Printing speed	200 mm/sec max	
Dot density (DPI)	203.2	
Dot pitch (mm)	0.125*0.125	
Effective printing width	72mm, 576dots	
Printing direction	Unidirectional with friction feed	
Character / Line	Font A Font B	(12*24) 42 columns (10*20) 56 columns
Paper	Type Width Thickness Roll diameter	Thermal paper 79.5mm (±0.5mm) 0.07mm 83 Ømm
Reliability	TPH Life MCBF	100km 60,000,000 lines
Character / Set	Alphanumeric character Extended graphic	95 128 x 35 page
Barcode	EAN-8, EAN-13, CODE39, CODE93, CODE128, ITF, UPC-A, UPC-E, CODABAR	
Emulation	ESC/POS command compatible	
Driver	Windows / OPOS	
Interface	USB + Serial combo / Ethernet / Wi-fi	
Power	DC 24V, 2.5A	
Data buffer	4 Kbyte	
Cutting	Life Cutting method	1,000,000 cuts Partial Cut / Full Cut
Temperature	Operation Storage	0 ~ 40°C -20 ~ 60°C
Qualification	CE, FCC, KC	
Dimension (WxHxD)	136 x 162.5 x 122(mm), 5.3 x 6.3 x 4.8(inch)	