

# Specifications



	AnyShop II Q SERIES	AnyShop II D25
<b>CPU</b>	uPGA988 for 3rd Generation Intel® Core™ i7/i5/i3 (Ivy Bridge), 2nd Generation Intel® Core™ (Sandy Bridge) - Intel® Core™ i7 3940XM Processor (8M Cache, up to 3.90 GHz)	Intel Atom processor D2550 (1MB Cache, 1.86 GHz, Dual Core for Cedarview-D)
<b>Chipset</b>	Intel QM77	Intel NM10
<b>Storage</b>	SATA 3 (6Gb/s) 2.5 inch HDD or SSD (Max. 2 Optional)	SATA 2 (3Gb/s) 2.5 inch HDD or SSD (Max. 2 Optional)
	Support Raid 0, 1	-
	Support AHCI	
<b>Memory</b>	DDR3-1600MHz SODIMM Default 2GB (MAX. 8GB)	DDR3-1066MHz SODIMM 2GB (MAX. 4GB)
<b>Graphic</b>	Integrated Intel GFX	Integrated Intel GMA HD 3650
<b>AMT</b>	Support iAMT 8.0	-
<b>Display</b>		
Resolution	15" LED Backlight LCD 250 cd/m <sup>2</sup> (1024 x 768 resolution)	
Touch screen	True Flat Capacitive or 5-wired Resistive Touch	5-wired Resistive Touch
<b>Internal I/O</b>		
USB	3 Ports (reserved for touch controller, MSR reader, mini PCIe)	
Serial port	COM 5 (reserved for cash drawer port) & COM 6 (reserved for MSR)	
Display port	LVDS or VGA & COM 4 (reserved for CDP)	VGA & COM 4 (reserved for CDP)
Extension slot	Mini PCIe	
Primary display	24bit LVDS	
<b>External I/O</b>		
USB	Rear 6 (USB 3.0 x 4 ports, USB 2.0 x 2 ports)	Rear 4 (USB 2.0 x 4 ports)
PS/2	1 Port (reserved for Keyboard & Mouse)	
Serial port	COM 1 ~ 3 with 5V/12V power output on 9pin	
LAN	Gigabit Ethernet x 2 ports 1x Intel Gigabit LAN with iAMT 8.0(Intel 82579LM) 1x Intel Gigabit LAN with (Intel 82583V)	Realtek RTL 8111E Ethernet Controller
Audio	Realtek ALC 892 / Line-out, Mic-in	
Display port	VGA x 1port	
<b>Options</b>		
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track	
Speaker	2 x 0.8W (Stereo)	
Side USB	4 Ports (USB 2.0 x 4 ports)	
SCR	EMV level 1	
Dallas	Dallas I-button reader	
Back up battery	Smart battery (supports up to 1 packs)	
Customer display	VFD type (20 x 2) Alphabet & numeric	
2nd LCD	10.1" LCD or 12.1" LCD or 15" LCD (1024 x 768 resolution)	
2nd Storage	2nd 2.5 inch HDD / SSD storage	
Cash drawer port	1 Port (RJ11 shared with COM5)	
Parallel port	1 Port	
WiFi	Mini PCIe for wireless LAN	
<b>Operating Temperature</b>	0°C ~ 40°C at 10% ~ 80% humidity	
<b>Storage Temperature</b>	-20°C ~ 60°C at 10% ~ 80% humidity	
<b>Qualification</b>	CE, FCC, KC	
<b>Power</b>	Adaptor 24V, 6A	Adaptor 12V, 5A
<b>OS Support</b>	Windows 7, Windows 8, POS Ready 7	Windows XP/Vista, Windows 7, POS Ready 2009/7
<b>Dimension (WxHxD)</b>	365 x 305 x 385(mm), 14.3 x 12 x 15.1(inch)	

\* Product specifications may differ according to region and may be changed without prior notice.