



## AnyShop

### High-Performance POS System That's Adaptable to Every Business Need

The ANYSHOP is a stand alone or wall-mountable panel POS system with advanced features and powerful functions. It includes built-in speakers and a video surveillance camera for complete control over loss prevention or for team member video conferencing.


The choice of either an Intel® Atom™ or Intel® Core™ i7/i5/i3 (Ivy Bridge) Celeron® Mobile processors allows for system flexibility.

Designed with longevity and maintenance in mind, the ANYSHOP's advanced modular design allows the HDD and optional peripheral devices to be easily mounted or removed without the need for cumbersome tools. The intuitive I/O connection panel provides optimum cable management underneath the system's base. The ANYSHOP's stylish design and color choices enables it to perfectly adapt into any retail or hospitality environment.



- Optimized High Performance, Energy Efficient Processor
- Wall-Mountable or Standalone, Easy to Install
- Standard Stereo Speakers and Optional Built-In Camera
- High-Tech Cooling System
- Optional Peripherals Install with Ease
- Available in a Variety of Colors

# What's special?



## ☒ AnyShop Any Space

Designed with the user's requirements in mind, AnyShop provides a smart solution for any cash wrap where space is at a premium. The AnyShop can easily be wall mounted, making it a perfect space saving solution for any hospitality, retail, or healthcare environment.



## ☒ Enhanced Stability HDD Bracket

Our unique HDD bracket has special shock absorbing rubberized posts that disperse vibrations away from the HDD that could potentially cause HDD damage. This feature lengthens HDD lifespan and decreases support calls.

## ☒ Power Cooling System Design

Our superior fanless design allows for low power consumption, maximum heat disbursement and optimal system performance.

Our fanless design ensures the internal housing is virtually maintenance/hassle free without having to worry over system fan failures.

## ☒ Simplified Maintenance

Removable slide-in HDD (screw-free).



External Power Supply Unit


External power supply design reduces machine internal heat production, and allows easier maintenance of the power supply should it need servicing.

The Best Price


Increased performance and an affordable choice with Intel Atom Dual Core CPU.

Different Colors Available

Just clip on/off to customize your POS.



Default Color



Customer's Color



# Options



Stereo Speakers



Magnetic Stripe Reader (MSR)  
Smart Card Reader (SCR)



Camera (optional)

- Loss Prevention
- Video conferencing



Customer Display

- VFD type
- 20 columns x 2 lines



2nd LCD Display

- 15", 12.1", 10.1" display
- 1024 x 768 resolution



# Specifications



	AnyShop Q SERIES	AnyShop D25
<b>CPU</b>	uPGA988 for 3rd Generation Intel® Core™ i7/i5/i3 (Ivy Bridge), 2nd Generation Intel® Core™ (Sandy Bridge) - Intel® Core™ i7 3940XM Processor (8M Cache, up to 3.90 GHz)	Intel Atom processor D2550 (1MB Cache, 1.86 GHz, Dual Core for Cedarview-D)
<b>Chipset</b>	Intel QM77	Intel NM10
<b>Storage</b>	SATA 3 (6Gb/s) 2.5 inch HDD or SSD	SATA 2 (3Gb/s) 2.5 inch HDD or SSD
	Support Raid 0, 1	-
	Support AHCI	
<b>Memory</b>	DDR3-1600MHz SODIMM Default 2GB (MAX. 8GB)	DDR3-1066MHz SODIMM 2GB (MAX. 4GB)
<b>Graphic</b>	Integrated Intel GFX	Integrated Intel GMA HD 3650
<b>AMT</b>	Support iAMT 8.0	-
<b>Display</b>		
Resolution	15" LED Backlight TFT-LCD 250 cd/m <sup>2</sup> (1024 x 768 resolution)	
Touch screen	5-wired Resistive Touch	
<b>Internal I/O</b>		
USB	3 Ports (reserved for touch controller, SCR EMV card, camera and MSR controller)	
Serial port	COM 5 (reserved for cash drawer port) & COM 6 (reserved for MSR)	
Display port	LVDS or VGA & COM 4 (reserved for CDP)	
Extension slot	Mini PCIe	
Primary display	24bit LVDS	
<b>External I/O</b>		
USB	Rear 6 (USB 3.0 x 4 ports, USB 2.0 x 2 ports)	Rear 4 (USB 2.0 x 4 ports)
PS/2	1 Port (reserved for Keyboard & Mouse)	
Serial port	COM 1 ~ 3 with 5V/12V power output on 9pin	
LAN	Gigabit Ethernet x 2 ports 1x Intel Gigabit LAN with iAMT 8.0(Intel 82579LM) 1x Intel Gigabit LAN with (Intel 82583V)	Realtek RTL 8111E Ethernet Controller
Audio	Realtek ALC 892 / Line-out, Mic-in	
Display port	VGA x 1 port	
<b>Options</b>		
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track	
Speaker	2 x 0.8W (Stereo)	
Camera	Camera	
Side USB	2 Ports (USB 2.0 x 2 ports)	
Serial port	COM5 (support 9pin header or DB9, shared with cash drawer port)	
SCR	EMV level 1	
Dallas	Dallas I-button reader	
Customer display	VFD type (20 x 2)	
2nd LCD	10.1" LCD or 12.1" LCD or 15" LCD (1024 x 768 resolution)	
Cash drawer port	1 port	
Parallel port	1 port	
WiFi	Mini PCIe for wireless LAN	
<b>Operating Temperature</b>	0°C ~ 40°C at 10% ~ 80% humidity	
<b>Storage Temperature</b>	-20°C ~ 60°C at 10% ~ 80% humidity	
<b>Qualification</b>	CE, FCC, KC, CCC	
<b>Power</b>	Adaptor 24V, 6A	Adaptor 12V, 5A
<b>OS Support</b>	Windows 7, Windows 8, POS Ready 7	Windows XP/Vista, Windows 7, POS Ready 2009/7
<b>Dimension (WxHxD)</b>	384 x 381 x 263(mm), 15.1 x 15 x 10.3(inch)	

\* Product specifications may differ according to region and may be changed without prior notice.