



## AnyShop PRO

Ultra High Performance with a  
Budget Price!  
New Style for 2014

ANYSHOP PRO is a modern looking POS system with multiple color options that allow it to match well with just about any décor. The ANYSHOP PRO boasts high performance, dependability and compatibility for the hospitality and retail verticals. Its

next generation Intel Atom energy efficient processor reduces power consumption and also reduces total cost of ownership. Simply put, the ANYSHOP PRO is one of the best POS systems you can buy today for your money.



- Stylish, Space Saving Design
- Eco Friendly : Saves Power & The Environment
- Energy Efficient Intel Atom CPU
- Fanless Deign Ensuring Years of Operation
- DDR3-1066MHz 2GB Memory (MAX. 4GB)
- LED Technology Offers Vibrant Video Graphics
- Industrial Grade Motherboard
- Shock Resistant Storage(HDD/SSD) Housing

# Options



Touch Screen with Flexible Angle Adjustment



Magnetic Stripe Reader (MSR)  
Smart Card Reader (SCR)



Available in a Variety of Colors



Black Red wine White

Customer Display

- VFD type
- 20 columns x 2 lines



2nd LCD Display

- 12.1", 10.1" display
- 1024 x 768 resolution



Stereo Speakers







## Specifications



AnyShop PRO	
<b>CPU</b>	Intel Atom processor D2550 (1MB Cache, 1.86 GHz, Dual Core for Cedarview-D)
<b>Chipset</b>	Intel NM10
<b>Storage</b>	SATA 2 (3Gb/s) 2.5 inch HDD or SSD, Support AHCI
<b>Memory</b>	DDR3-1066MHz SODIMM 2GB (MAX. 4GB)
<b>Graphic</b>	Integrated Intel GMA HD 3650
<b>Display</b>	
Resolution	15" LED Backlight TFT-LCD 250 cd/m <sup>2</sup> (1024 x 768 resolution)
Touch screen	5-wired Resistive Touch
<b>Internal I/O</b>	
USB	3 Ports (reserved for touch controller, SCR EMV card, MSR controller)
Serial port	COM 5 (reserved for cash drawer port) & COM 6 (reserved for MSR)
Display port	VGA & COM 4 (reserved for CDP)
Extension slot	Mini PCIe
Primary display	24bit LVDS
Speaker	2 x 0.8W (Stereo)
<b>External I/O</b>	
USB	Rear 4 (USB 2.0 x 4 ports)
PS/2	1 Port (reserved for Keyboard & Mouse)
Serial port	COM 1 ~ 3 with 5V/12V power output on 9pin
LAN	Realtek RTL 8111E Ethernet Controller
Audio	Realtek ALC 892 / Line-out, Mic-in
Display port	VGA x 1 port
<b>Options</b>	
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track
Side USB	2 Ports (USB 2.0 x 2 ports)
SCR	EMV level 1
Dallas	Dallas I-button reader
Customer display	VFD type (20 x 2)
2nd LCD	10.1" LCD or 12.1" LCD (1024 x 768 resolution)
WiFi	Mini PCIe for wireless LAN
<b>Operating Temperature</b>	0°C ~ 40°C at 10% ~ 80% humidity
<b>Storage Temperature</b>	-20°C ~ 60°C at 10% ~ 80% humidity
<b>Qualification</b>	CE, FCC, KC
<b>Power</b>	Adaptor 12V, 5A
<b>OS Support</b>	Windows XP/Vista, Windows 7, POS Ready 2009/7
<b>Dimension (WxHxD)</b>	384 x 381 x 263(mm), 15.1 x 15 x 10.3(inch)

\* Product specifications may differ according to region and may be changed without prior notice.