



- Paper Jam-Recovery Printer
- Ultra-Fast Printing Speed (Up to 220mm/sec)
- Specially Designed Font Provides Superior Readability
- Easy Maintenance
- High Resolution to 203dpi
- Supports Various Interfaces (USB & Serial Combo/Parallel/Ethernet/Wi-fi)
- Easy Paper Loading
- Available Extension Melody
- Windows & OPOS Drivers
- Epson Compatible

Specifications



A10M		
Printing method	3" Jam direct thermal	
Printing speed	220 mm/sec max	
Dot density (DPI)	203.2	
Dot pitch (mm)	0.125*0.125	
Effective printing width	74mm, 588dots	
Printing direction	Unidirectional with friction feed	
Character / Line	Font A Font B	(14*28) 42 columns (10*20) 58 columns
Paper	Type Width Thickness Roll diameter	Thermal paper 80 or less 0.07mm 80 Ømm
Reliability	TPH Life MCBF	100km 60,000,000 lines
Character / Set	Alphanumeric character Extended graphic	95 128 x 35 page
Barcode	EAN-8, EAN-13, CODE39, CODE93, CODE128, ITF, UPC-A, UPC-E, CODABAR, QR CODE	
Emulation	ESC / POS command compatible	
Driver	Windows / OPOS	
Function	Black Mark Detection	
Interface	USB+Serial combo / Parallel / Ethernet / Wi-fi	
Power	DC 24V, 2.5A	
Data buffer	4 Kbyte	
Cutting	Life Cutting method	1,000,000 cuts Partial Cut
Temperature	Operation Storage	0 ~ 40°C -20 ~ 60°C
Qualification	CE, FCC, KC	
Dimension (WxHxD)	142 x 201 x 126(mm), 5.5 x 7.9 x 4.9(inch)	